

Angenieux SUPER TELE Zoom  
ENG lens  
40x11 AIF HD - 40x15 AIF HD

Ref. : T40x11 BESSD HD,  
T40x15 BESSD HD



<b>Zoom ratio :</b>	40x	40x
<b>Focal length :</b>	11 - 440 mm 22 - 880 mm (with 2x)	15 - 600 mm 30 - 1200 mm (with 2x)
<b>Aperture :</b>	f/2 (11 - 230 mm) f/4 (440 mm) f/4 (22 - 460 mm) (with 2x) f/8 (860 mm) (with 2x)	f/2.7 (15 - 310 mm) f/5.4 (600 mm) f/5.4 (30 - 620 mm) (with 2x) f/10.8 (1200 mm) (with 2x)
<b>MOD :</b>	2.2 m - 7'8"	2.2 m - 7'8"
<b>Macro :</b>	10 mm	10 mm
<b>Extender :</b>	2x	2x

- Digital servo control :**
- > Large variety of modes for zoom and focus servo controls.
  - > Serial interface for digital remote control.
  - > Anti-breathing mode keeps field of view constant when focusing.
  - > Assisted Internal Focus.
  - > Auto cruise.
  - > Iris Priority : the zoom range stops when the lens starts to ramp.

**BESSD :** Digital version with built in servo focus

<b>Front diam. :</b>	132 mm	132 mm
<b>Weight (approx.) :</b>	5.95 kg - 13.1 lbs	6.05 kg - 13.3 lbs
<b>Length :</b>	360 mm	377 mm
<b>UV filter included :</b>	M125 x 1	M125 x 1



Aspect ratio (2/3" video)	16/9 aspect ratio (9.6x5.4 mm) 40x11				16/9 aspect ratio (9.6x5.4 mm) 40x15			
<b>Focal Length</b>	11 mm	440 mm	22 mm (2x)	880 mm (2x)	15 mm	600 mm	30 mm (2x)	1200 mm (2x)
<b>Horizontal angular field of view</b>	47.2°	1.2°	24.6°	0.7°	35.5°	1°	18°	0.5°
<b>Object dimensions at MOD (mm)</b>	1759x994	45x25	881x496	22x13	1287x723	33x19	643x361	16x9