

Angenieux SUPER TELE Zoom
ENG lens
40x11 AIF HR - 40x15 AIF HR

Ref. : T40x11 BESSD HR,
T40x15 BESSD HR



Zoom ratio :	40x	40x
Focal length :	11 - 440 mm 22 - 880 mm (with 2x)	15 - 600 mm 30 - 1200 mm (with 2x)
Aperture :	f/2 (11 - 230 mm) f/4 (440 mm) f/4 (22 - 460 mm) (with 2x) f/8 (880 mm) (with 2x)	f/2.7 (15 - 310 mm) f/5.4 (600 mm) f/5.4 (30 - 620 mm) (with 2x) f/10.8 (1200 mm) (with 2x)
MOD :	2.2 m - 7'8"	2.2 m - 7'8"
Macro :	10 mm	10 mm
Extender :	2x	2x

Digital servo control :

- > Large variety of modes for zoom and focus servo controls.
- > Serial interface for digital remote control.
- > Anti-breathing mode keeps field of view constant when focusing.
- > Assisted Internal Focus.
- > Auto cruise.
- > Iris Priority : the zoom range stops when the lens starts to ramp.

BESSD : Digital version with built in servo focus

Front diam. :	132 mm	132 mm
Weight (approx.) :	5.95 kg - 13.1 lbs	6.05 kg - 13.3 lbs
Length :	360 mm	377 mm
UV filter included :	M125 x 1	M125 x 1



Aspect ratio (2/3" video)	4/3 aspect ratio (8.8x6.6 mm) 40x11				4/3 aspect ratio (8.8x6.6 mm) 40x15			
Focal Length	11 mm	440 mm	22 mm (2x)	880 mm (2x)	15 mm	600 mm	30 mm (2x)	1200 mm (2x)
Horizontal angular field of view	43.6°	1°	22.6°	0.5°	32.6°	0.7°	16.6°	0.3°
Object dimensions at MOD (mm)	1615x1214	41x31	808x606	20x15	1180x885	30x22	590x441	15x11